

CRYSTAL PRODUCTS

Issued 2024

Tuning Fork Crystal Units
(kHz range)



Crystal Unit with built-in temperature sensor
(MHz range)



Crystal Unit
(MHz range)



SPXO



TCXO



VCXO



OCXO




Frequency Synthesizer



Millimeter-wave converter



Optical Component



QCM Sensor



Ultrasound Probe
(Transducer)



SAW Devices













This catalog shows products and specifications of our main range.
Please contact our sales representatives or visit our website (<https://www.ndk.com/>) with your inquiries.







■ Tuning Fork Crystal Units (kHz range)

NX1610SA (1.6×1.0×0.45mm) NX2012SA (2.0×1.2×0.55mm) NX3215SA (3.2×1.5×0.8mm)  	  	Ultra compact size tuning fork crystal unit (kHz range) Nominal Frequency : 32.768kHz Frequency Tolerance : $\pm 20 \times 10^{-6}$ Operating Temperature Range : -40 to +85°C
NX2012SA (2.0×1.2×0.55mm) NX3215SA (3.2×1.5×0.8mm)   	 	Compact size tuning fork crystal unit (kHz range) for Automotive Nominal Frequency : 32.768kHz Frequency Tolerance : $\pm 20 \times 10^{-6}$ Operating Temperature Range : -40 to +125°C Conforms to AEC-Q200
NX3215SD (3.2×1.5×0.8mm)   		Compact size tuning fork crystal unit (kHz range) for Automotive. Enhanced products of solder cracking resistance. Nominal Frequency : 32.768kHz Frequency Tolerance : $\pm 20 \times 10^{-6}$ Operating Temperature Range : -40 to +125°C Conforms to AEC-Q200
NX1610SE (1.6×1.0×0.45mm) NX2012SE (2.0×1.2×0.55mm) NX3215SE (3.2×1.5×0.8mm)  	  	Ultra compact size tuning fork crystal unit (kHz range) with low ESR (Equivalent Series Resistance) Nominal Frequency : 32.768kHz Frequency Tolerance : $\pm 20 \times 10^{-6}$ Operating Temperature Range : -40 to +85°C
NX2012SF (2.0×1.2×0.55mm) NX3215SF (3.2×1.5×0.8mm)  	 	Compact size tuning fork crystal unit (kHz range) for specially controlled medical devices class 3 Nominal Frequency : 32.768kHz Frequency Tolerance : $\pm 20 \times 10^{-6}$ Operating Temperature Range : -40 to +125°C

■ Crystal Unit with built-in temperature sensor (MHz range)











NX1612SD (1.6×1.2×0.65mm)  		Ultra compact size crystal unit with built-in thermistor Nominal Frequency Range : 26 to 160MHz Frequency Tolerance : $\pm 10 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 12 \times 10^{-6}$ / -30 to +85°C
NX2016SF (2.0×1.6×0.65mm)  		Compact size crystal unit with built-in thermistor Nominal Frequency Range : 19.2 to 55.2MHz Frequency Tolerance : $\pm 10 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 12 \times 10^{-6}$ / -30 to +85°C
NX2016SF (2.0×1.6×0.65mm)   		Compact size crystal unit with built-in thermistor for Automotive Nominal Frequency Range : 19.2 to 55.2MHz Frequency Tolerance : $\pm 10 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 25 \times 10^{-6}$ / -40 to +105°C Conforms to AEC-Q200

■ Crystal Unit (MHz range)

NX1008AA (1.0×0.8×0.25mm)  		Ultra compact size crystal unit (1.0×0.8mm) Nominal Frequency Range : 32 to 64MHz Frequency Tolerance : $\pm 10 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 10 \times 10^{-6}$ / -30 to +85°C Nominal Frequency Range : 64 to 160MHz Frequency Tolerance : $\pm 15 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 12 \times 10^{-6}$ / -30 to +85°C
NX1210AB (1.2×1.0×0.25mm)  		Ultra compact size crystal unit (1.2×1.0mm) Nominal Frequency Range : 24 to 64MHz Frequency Tolerance : $\pm 10 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 10 \times 10^{-6}$ / -30 to +85°C Nominal Frequency Range : 64 to 160MHz Frequency Tolerance : $\pm 15 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 12 \times 10^{-6}$ / -30 to +85°C








NX1612SA (1.6×1.2×0.3mm)  		Ultra compact size crystal unit (1.6×1.2mm) Nominal Frequency Range : 24 to 64MHz Frequency Tolerance : $\pm 10 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 10 \times 10^{-6}$ / -30 to +85°C Nominal Frequency Range : 64 to 160MHz Frequency Tolerance : $\pm 15 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 12 \times 10^{-6}$ / -30 to +85°C
NX2016SA (2.0×1.6×0.45mm)  		Compact size crystal unit (2.0×1.6mm) Nominal Frequency Range : 16 to 80MHz Frequency Tolerance : $\pm 10 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 25 \times 10^{-6}$ / -40 to +85°C
NX2520SA (NRND) (2.5×2.0×0.5mm)  		Compact size crystal unit (2.5×2.0mm) Nominal Frequency Range : 16 to 80MHz Frequency Tolerance : $\pm 15 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 25 \times 10^{-6}$ / -40 to +85°C
NX1612SA (1.6×1.2×0.3mm)   		Ultra compact size crystal unit (1.6×1.2mm) for Automotive Nominal Frequency Range : 24 to 80MHz Frequency Tolerance : $\pm 15 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 50 \times 10^{-6}$ / -40 to +125°C Conforms to AEC-Q200
NX2016GC (2.0×1.6×0.70mm)  		Compact size crystal unit (2.0×1.6mm) for Automotive Nominal Frequency Range : 16 to 54MHz Frequency Tolerance : $\pm 50 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 150 \times 10^{-6}$ / -40 to +150°C Conforms to AEC-Q200
NX2016SA (2.0×1.6×0.45mm)   		Compact size crystal unit (2.0×1.6mm) for Automotive Nominal Frequency Range : 16 to 80MHz Frequency Tolerance : $\pm 15 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 50 \times 10^{-6}$ / -40 to +125°C Conforms to AEC-Q200
NX3225GA (3.2×2.5×0.75mm)  		Crystal unit for Automotive (Excellent environment-resistant performance) Nominal Frequency Range : 9.8 to 62.4MHz Frequency Tolerance : $\pm 50 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 150 \times 10^{-6}$ / -40 to +150°C Conforms to AEC-Q200
NX3225GB (3.2×2.5×0.75mm)  		Crystal unit for Automotive (High resistance to solder cracking) Nominal Frequency Range : 12 to 62.4MHz Frequency Tolerance : $\pm 50 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 150 \times 10^{-6}$ / -40 to +150°C Conforms to AEC-Q200
NX3225GD (3.2×2.5×0.8mm)  		Crystal unit for Automotive (Low Frequency, High resistance to solder cracking) Nominal Frequency Range : 8 to 12MHz Frequency Tolerance : $\pm 50 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 150 \times 10^{-6}$ / -40 to +150°C Conforms to AEC-Q200
NX3225SA (3.2×2.5×0.55mm)   		Compact size crystal unit (3.2×2.5mm) for Automotive Nominal Frequency Range : 12 to 80MHz Frequency Tolerance : $\pm 15 \times 10^{-6}$ Frequency / Temperature Characteristics : $\pm 50 \times 10^{-6}$ / -40 to +125°C Conforms to AEC-Q200
RC-8 (φ15.60×4.80mm) 		High reliability crystal unit for OCXO with excellent frequency stability HC-37/U equivalent low profile Nominal Frequency Range : 5 to 20MHz Frequency Tolerance : $\pm 3 \times 10^{-6}$ Operating Temperature Range : -40 to +120°C
NC-18C (11.45×5.00×13.46mm) 		High reliability crystal unit for OCXO with excellent frequency stability HC-43/U equivalent Nominal Frequency Range : 10 to 20MHz Frequency Tolerance : $\pm 3 \times 10^{-6}$ Operating Temperature Range : -40 to +120°C













■ Simple Packaged Crystal Oscillator (SPXO)

Support to 125°C NZ1612SH / MHz (1.6×1.2×0.6mm) NZ2016SH / NZ2016SEB / MHz (2.0×1.6×0.7mm) NZ2520SH / NZ2520SEB / MHz (2.5×2.0×0.9mm)  	  	Supports a wide temperature range from -40 to +125°C Clock Oscillator Nominal Frequency Range : 7.5 to 80MHz (NZ1612SH) 6.5 to 160MHz (NZ2016SH) 1.5 to 6.5MHz (NZ2016SEB) 5.5 to 160MHz (NZ2520SH) 1.5 to 5.5MHz (NZ2520SEB) Output Specification : CMOS Supply Voltage [V _{CC}] : +1.8V, +2.5V, +3.0V, +3.3V Overall Frequency Tolerance : $\pm 100 \times 10^{-6}$ / -40 to +125°C
NT2016SEA (2.0×1.6×0.8mm) NT2520SEA (2.5×2.0×0.9mm)   	 	High precision type Clock Oscillator for Automotive Nominal Frequency Range : 10 to 52MHz Output Specification : CMOS Supply Voltage [V _{CC}] : +1.8V, +2.5V, +3.0V, +3.3V Overall Frequency Tolerance : $\pm 10 \times 10^{-6}$ / -40 to +105°C Conforms to AEC-Q100/200











NZ1612SHB / kHz (1.6×1.2×0.6mm) NZ2016SHB / kHz (2.0×1.6×0.7mm) NZ2520SHB / kHz (2.5×2.0×0.9mm)  		Low current consumption and wide temperature range from -40 to +125°C Clock Oscillator Nominal Frequency : 32.768kHz Output Specification : CMOS Supply Voltage [V _{CC}] : +1.8V, +2.5V, +3.0V, +3.3V Overall Frequency Tolerance : ±100×10 ⁻⁶ / -40 to +125°C Current Consumption (During Operation) : Max. 32 μA
NZ2016SHA / MHz / kHz (2.0×1.6×0.7mm) NZ2520SHA / MHz / kHz (2.5×2.0×0.9mm)   		High quality and high reliability design for Automotive safety Clock Oscillator Nominal Frequency Range : 6.5 to 160MHz 32.768kHz (NZ2016SHA) 5.5 to 160MHz 32.768kHz (NZ2520SHA) Output Specification : CMOS Supply Voltage [V _{CC}] : +1.8V, +2.5V, +3.0V, +3.3V Overall Frequency Tolerance : ±100×10 ⁻⁶ / -40 to +125°C Conforms to AEC-Q100/200
Support to ±25ppm NZ2520SEB / MHz (2.5×2.0×0.9mm)  		High precision type Clock Oscillator Nominal Frequency Range : 1.5 to 80MHz Output Specification : CMOS Supply Voltage [V _{CC}] : +1.8V, +2.5V, +3.0V, +3.3V Overall Frequency Tolerance : ±25×10 ⁻⁶ / -40 to +85°C
NZ2520SDA / MHz (2.5×2.0×0.9mm)  		Ultra low phase noise type, ultra low phase jitter type Clock Oscillator Nominal Frequency Range : 20 to 54MHz Output Specification : CMOS Phase Noise (22.5792MHz) : Typ. -169dBc / Hz at 100kHz, +3.3V, +25°C Supply Voltage [V _{CC}] : +1.8V, +2.5V, +3.0V, +3.3V Overall Frequency Tolerance : ±50×10 ⁻⁶ / -40 to +85°C
NP2520SA NEW (2.5×2.0×0.8mm) NP2520SAB NEW (2.5×2.0×0.8mm)  		Differential output SPXO Nominal Frequency Range : 100 to 170MHz Output Specification : LVPECL Supply Voltage [V _{CC}] : +2.5V, +3.3V Overall Frequency Tolerance : Max. ±50×10 ⁻⁶ / -40 to +105°C Phase Jitter : Typ. 68fs (SA) Typ. 40fs (SAB) (Offset Frequency : 12kHz to 20MHz) @156.25MHz
NP3225SAA NEW (3.2×2.5×0.9mm) NP3225SBA NEW (3.2×2.5×0.9mm) NP3225SCA NEW (3.2×2.5×0.9mm)   		Differential output SPXO for Automotive Nominal Frequency Range : 100 to 170MHz Output Specification : LVPECL (SAA) LVDS (SBA) HCSL (SCA) Supply Voltage [V _{CC}] : +2.5V to +3.3V (SBA) +3.3V (SAA, SCA) Overall Frequency Tolerance : Max. ±50×10 ⁻⁶ / -40 to +105°C Phase Jitter : Typ. 90fs @156.25MHz (SAA) Typ. 90fs @150MHz (SBA) Typ. 100fs @156.25MHz (SCA) (Offset Frequency : 12kHz to 20MHz)
NP5032S[] (5.0×3.2×1.2mm) NP7050S[] (7.0×5.0×1.6mm)  		Multi mode crystal oscillator (Available for customizing specifications by frequency selection function) Nominal Frequency Range : 15 to 2100MHz Frequency Selection Function : Single, Dual, Quad, Any Rate Output Specification : CMOS, LVPECL, LVDS, CML, HCSL Supply Voltage [V _{CC}] : +1.8V, +2.5V, +3.3V Overall Frequency Tolerance : Max. ±10×10 ⁻⁶ / -40 to +85°C (Narrow Tolerance) Max. ±50×10 ⁻⁶ / -40 to +85°C (Standard)

■ Temperature Compensated Crystal Oscillator (TCXO)







NT1612SA (1.6×1.2×0.55mm) NT2016SA (2.0×1.6×0.8mm) NT2520SB (2.5×2.0×0.9mm)  		TCXO for high precision GPS Nominal Frequency Range : 26 to 52MHz Supply Voltage [V _{CC}] : +1.8V, +3.3V Frequency / Temperature Characteristics : Max. ±0.5×10 ⁻⁶ / -30 to +85°C
NT2016SE (2.0×1.6×0.8mm) NT2520SE (2.5×2.0×0.9mm)   		Supports a wide temperature range from -40 to +105°C for Automotive (TCXO) Nominal Frequency Range : 10 to 52MHz Supply Voltage [V _{CC}] : +1.8V, +3.3V Frequency / Temperature Characteristics : Max. ±0.5×10 ⁻⁶ / -40 to +105°C Conforms to AEC-Q100/200

NT2016SJA (2.0×1.6×0.8mm)  		Low phase noise characteristics and stand-by function (TCXO) Nominal Frequency Range : 16 to 76.8MHz Supply Voltage [V _{CC}] : +1.8V, +3.3V Frequency / Temperature Characteristics : Max. $\pm 0.5 \times 10^{-6}$ / -30 to +85°C
NT2016SHC (2.0×1.6×0.8mm) NT2520SHC (2.5×2.0×0.9mm)   	 	Supports high temperature range from -40 to +125°C for Automotive and stand-by function (TCXO) Nominal Frequency Range : 26 to 100MHz Supply Voltage [V _{CC}] : +1.8V, +3.3V Frequency / Temperature Characteristics : Max. $\pm 3 \times 10^{-6}$ / -40 to +125°C Conforms to AEC-Q100/200
NT5032BB (5.0×3.2×1.8mm) NT7050BB (7.0×5.0×2.0mm)  	 	High Precision TCXO for 5G and Stratum 3 Nominal Frequency Range : 10 to 56MHz Supply Voltage [V _{CC}] : +3.3V Frequency / Temperature Characteristics : Max. $\pm 0.1 \times 10^{-6}$ / -40 to +105°C Current Consumption : Max. 10mA With Enable / Disable (Stand-by) function.





■ Voltage Controlled Crystal Oscillator (VCXO)

NV2520SA (2.5×2.0×0.9mm)  		Compact size VCXO Nominal Frequency Range : 11 to 40MHz Output Specification : CMOS Overall Frequency Tolerance : Max. $\pm 50 \times 10^{-6}$ / -40 to +85°C Frequency Control Range / Control Voltage : Min. $\pm 100 \times 10^{-6}$ / +1.65±1.65V
NV5032SC (5.0×3.2×1.2mm)  		VCXO for communication equipment and base station Nominal Frequency : 122.88MHz Output Specification : LVPECL Supply Voltage [V _{CC}] : +3.3V Overall Frequency Tolerance : Max. $\pm 50 \times 10^{-6}$ / -40 to +105°C Frequency Control Range / Control Voltage : Min. $\pm 100 \times 10^{-6}$ / +1.65±1.65V
NV5032S[] (5.0×3.2×1.2mm) NV7050S[] (7.0×5.0×1.6mm)  	 	Multi mode crystal oscillator (Available for customizing specifications by frequency selection function) Nominal Frequency Range : 15 to 2100MHz Frequency Selection Function : Single, Dual, Quad, Any Rate Output Specification : LVPECL, LVDS, CML, HCSSL Supply Voltage [V _{CC}] : +1.8V, +2.5V, +3.3V Overall Frequency Tolerance : Max. $\pm 10 \times 10^{-6}$ / -40 to +85°C (Narrow Tolerance) Max. $\pm 50 \times 10^{-6}$ / -40 to +85°C (Standard) Selection of Frequency Control Range : Min. $\pm 50 \times 10^{-6}$ to Min. $\pm 250 \times 10^{-6}$





■ Oven Controlled Crystal Oscillator (OCXO)

NH7050SA (7.0×5.0×3.3mm) 		Ultra small size OCXO (7×5mm) Nominal Frequency : 10,20,30,72,38.88MHz Supply Voltage [V _{CC}] : +3.3V Frequency / Temperature Characteristics : Max. $\pm 20 \times 10^{-9}$ / -40 to +95°C Power Consumption : at stable Max. 0.6W Long-term Frequency Stability : Max. 300×10^{-9} / year
NH25M22WG (25.4×22×11mm) 		Supports a wide temperature range OCXO (-40 to +85°C) Nominal Frequency : 10MHz Supply Voltage [V _{CC}] : +3.3V Frequency / Temperature Characteristics : Max. $\pm 10 \times 10^{-9}$ / -40 to +85°C Power Consumption : at stable Max. 1.3W Long-term Frequency Stability : Max. 50×10^{-9} / year Low Near-carrier Phase Noise Characteristics : -100dBc / Hz at 1Hz offset
NH26M26LC (26×26×12.5mm) 		Low phase noise and high stability OCXO Nominal Frequency : 10MHz Supply Voltage [V _{CC}] : +5.0V Frequency / Temperature Characteristics : Max. $\pm 10 \times 10^{-9}$ / -40 to +85°C Power Consumption : at stable Max. 1.3W Long-term Frequency Stability : Max. 50×10^{-9} / year Low Near-carrier Phase Noise Characteristics : -100dBc / Hz at 1Hz offset










■ Frequency Synthesizer

S6R6G6R6GA (140×70×22mm) 		For commercial radio equipment, microwave radio link, and digital radio Frequency Range : 6570.50 to 6589.75MHz Frequency Setting Resolution : 125kHz step Frequency Stability : Depends on External Reference Signal Within $\pm 5 \times 10^{-6}$ / 10 years (Internal TCXO Stability) SSB Phase Noise : Max. -47dBc (Integrated value of 1kHz to 2MHz)
S010G010GA (110×60×22mm) 		For local oscillator for microwave radios reference signal of radar system or measurement equipment Frequency Range : 4GHz to 10GHz Frequency Setting Resolution : 1MHz step Frequency Stability : Depends on External Reference Signal Max. $\pm 3 \times 10^{-6}$ / 10 years (Internal TCXO Stability) Spurious Non-harmonics : Max. -60dBc SSB Phase Noise : Typ. -80dBc / Hz at 1kHz (@4GHz) We offer custom design services that match required specifications and applications, even more radar system, etc., by setting with frequency ranges, high-speed frequency switching, low phase noise etc.



■ Millimeter-wave converter

C057G064GB (138×138×214mm) 		For measurement of in-vehicle millimeter-wave radar, motion sensor, industrial sensor RF Input Frequency Range : 57GHz to 64GHz IF Output Frequency Range : 1GHz to 8GHz Local Frequency : 56GHz Local Signal Phase Noise Max. -110dBc/Hz at 1MHz Conversion Gain : 26dB±1.5dB (Room Temp.)
C076G081GB (138×138×214mm) 		For measurement of in-vehicle millimeter-wave radar RF Input Frequency Range : 76GHz to 81GHz IF Output Frequency Range : 2GHz to 7GHz Local Frequency : 74GHz Local Signal Phase Noise Max. -114dBc/Hz at 1MHz Conversion Gain : 10dB±1.5dB (Room Temp.)


■ Optical Component

Optical Low-pass Filter  		An optical low pass filter is used to eliminate false signal that causes color Moiré fringes and false colors. You can choose also LiNbO3 wafer other than quartz to reduce total thickness of the filter. Additionally, NDK can take care of the bonding with filter glasses and processing of coating, side edge black coating, and adhesion of the frame.
Crystal Wavelength Plate  		According to your request regarding wavelength and phase accuracy, dependence of phase accuracy (temperature, incidence angle, wavelength) , you can choose from 3 different waveplate types; Compound zero-order type, Multiple-order type, True zero-order type. In addition, Air-gap type which are used High purity quartz crystal and Optical contact type without glue are available as for high-power laser application. Filter up to 4 inch is available, taking advantage of the strength of crystal growth in-house.
Optical filter  		NDK can provide any designed optical filter by combining the various wafer line-ups and technologies of coating, bonding, inspection method. Radiation-resistant quartz crystal filters are also available for use in nuclear power generation and space environments. Wafer: Quartz, Sapphire, Synthetic Quartz Glass, Optical Glass, Absorption Glass (UV, IR, ND) Coating technology : UVIR-cut, AR, ND, Band-pass coating, conductive coating (ITO), water-repellent coating

■ QCM Sensor































NAPiCOS ^{(*)1} series / NAPiCOS Lite & NAPiCOS Auto		NAPiCOS series / NAPiCOS Lite & NAPiCOS Auto NAPiCOS Lite & NAPiCOS Auto with QCM technology base can be used for real time monitoring for Immuno-reaction, Protein binding, DNA binding, etc. ^{(*)1} NAPiCOS is a coined word created by NDK, combining the words "nano", "pico" and "sensor"
Twin-QCM system		Twin-QCM System / Outgas sensor / Process Monitor It can be used for outgas measurement of various materials, environmental monitor, and real-time process monitor for semiconductor manufacturing equipment by monitoring the frequency (mass) change caused by absorption and desorption of substances to the crystal sensor with precise temperature control. *QCM : Quartz Crystal Microbalance

■ Ultrasound Probe (Transducer)


Product for 2D imaging & 3D imaging 		NDK has a probe line up for each application and can produce customer's designed products *Customers can decide a specification (frequency, element pitch and element number etc.) *NDK can design an outer shape as per customer's request Moreover, the attestation of "ISO13485:2016" that is International Standard of the quality management system in medical devices acquired, and we will deliver secure, safe and high-quality product for medical devices.
---	---	--

■ SAW Devices (Manufactured by NDK SAW devices Co., Ltd.)

More information : <https://www.sitorf.com/en/index.html>

WFB69A0866CF (3.0×3.0×1.25mm)  		For short range wireless Saw filter Nominal Frequency : 866.5MHz Insertion Attenuation : Max. 2.5dB Pass Bandwidth : ±3.5MHz Operating Temperature Range : -30 to +80°C Terminating Impedance : 50 Ω
WF998C0915CE (3.0×3.0×1.25mm)  		For short range wireless Saw filter Nominal Frequency : 915MHz Insertion Attenuation : Max. 2.5dB Pass Bandwidth : ±13MHz Operating Temperature Range : -30 to +80°C Terminating Impedance : 50 Ω
WFC11B0922CG (3.0×3.0×1.05mm)  		For short range wireless Saw filter Nominal Frequency : 922.5MHz Insertion Attenuation : Max. 3.5dB Pass Bandwidth : ±2MHz Operating Temperature Range : -20 to +85°C Terminating Impedance : 50 Ω
WFD79C0925FG (1.4×1.1×0.5mm)  		For short range wireless Saw filter Nominal Frequency : 925.8MHz Insertion Attenuation : Max. 3.0dB Pass Bandwidth : Min. 4.6MHz Operating Temperature Range : -25 to +75°C Terminating Impedance : 50 Ω
WFC93B0429CL (3.0×3.0×1.05mm)  		For specified low power radio Saw filter Nominal Frequency : 429.42MHz Insertion Attenuation : Max. 3.5dB Pass Bandwidth : ±0.5MHz Operating Temperature Range : -20 to +70°C Terminating Impedance : 50 Ω
WFC30B0924FF (1.4×1.1×0.5mm)  		For specified low power radio Saw filter Nominal Frequency : 924MHz Insertion Attenuation : Max. 3.2dB Pass Bandwidth : 8MHz Operating Temperature Range : -40 to +85°C Terminating Impedance : 50 Ω
WFG63D0315CG (3.0×3.0×1.05mm)   		For RKE (Remote keyless entry system) Saw filter Nominal Frequency : 315MHz Insertion Attenuation : Max. 2.0dB Pass Bandwidth : 1MHz Operating Temperature Range : -40 to +105°C Terminating Impedance : 50 Ω Conforms to AEC-Q200
WFC75C1472CE (3.0×3.0×1.05mm)   		For Automotive Satellite radio Saw filter Nominal Frequency : 1472MHz Insertion Attenuation : Max. 3.2dB Pass Bandwidth : 40MHz Operating Temperature Range : -40 to +125°C Terminating Impedance : 50 Ω Conforms to AEC-Q200
WFF93A1582UE (1.4×1.1×0.6mm)   		For Automotive GPS / GLONASS / BEIDOU. Nominal Frequency : 1582.355MHz Insertion Attenuation : Max. 2.0dB Pass Bandwidth : 46.61MHz Operating Temperature Range : -40 to +85°C Terminating Impedance : 50 Ω Conforms to AEC-Q200

Group Networks



NDK Europe Ltd.

Phone : +44-20-8547-0500
E-Mail : NDK@uk.ndk.com

NDK Europe Ltd. French Office

Phone : +33-1-60-95-0000
E-Mail : NDK@fr.ndk.com

NDK Europe Ltd. Italy Office

Phone : +39-02-96702920
E-Mail : NDK@it.ndk.com

Asian NDK Crystal Sdn. Bhd. Sales Dept

Phone : +60-3-5192-3360
E-Mail : ndks@sin.ndk.com

NDK Crystal Asia Pte. Ltd.

Phone : +65-6298-9878
E-Mail : ndks@sin.ndk.com

Suzhou NDK Co., Ltd. Sales Dept.

Phone : +86-5126-8252071
E-Mail : ndkchina-m@sh.ndk.com

NDK Electronics (HK) Limited Taipei Branch

Phone : +886-2-2555-0232
E-Mail : sales@tp.ndk.com

NDK Electronics Shanghai Co., Ltd.

Phone : +86-21-6278-5115
E-Mail : ndkchina-m@sh.ndk.com

NDK Electronics Shanghai Co., Ltd. Shenzhen Branch

Phone : +86-755-22182269
E-Mail : ndkchina-m@sh.ndk.com

NDK America, Inc.

Phone : +1-847-852-4165
E-Mail : sales@ndkxstal.com

NDK America, Inc. Silicon Valley Office

Phone : +1-408-428-0800
E-Mail : sales@ndkxstal.com

NDK America, Inc. Orange County Office

Phone : +1-949-444-3882
E-Mail : sales@ndkxstal.com

Note

- This catalog lists current information as of March 2024.
The products shown in this catalog may be subject to change or their production may be discontinued without prior notice.
- Names of companies or products described in this catalog are trademarks or registered trademarks of the respective companies.
- All product specifications in this catalog are provided for reference purposes only.
Before you use a product, please check its specifications with the "Specifications for delivery" issued at the time of contract.
Under no circumstances shall the Company be liable for any product failure resulting from any handling or operation of the product beyond the scope of its guarantee.
- Data contained in this catalog, such as various property data, are provided for the purpose of reference only.
Should this data give rise to any dispute relating to any intellectual property rights or any rights of a third party, the company shall not be liable to indemnify any party for any damage.
Their disclosure must not be construed as the granting of a license to use any of the intellectual property rights owned by the Company.
- If you intend to use products listed in this catalog for any applications that may result in loss of life or assets (controls relating to safety, medical, aeronautical, space equipment, etc.), it is absolutely essential that you must inform us of the intended application of the product.
- When products listed in this catalog are regarded as regulated goods under the "Foreign Exchange and Foreign Trade Act," an export license issued by the Japanese government in accordance with the Act will be required when exporting such products.
- With reference to ozone depleting substances (ODS), the Company's production processes are compliant to the terms stipulated in the Montreal Protocol.
- Information contained in this catalog must not be quoted, reproduced or used for any other purpose, including processing, either in part or in full without obtaining prior approval from the Company.



NIHON DEMPA KOGYO CO.,LTD.

Head Office

Merkmal Keio Sasazuka Bldg.,
1-47-1, Sasazuka, Shibuya-ku,
Tokyo 151-8569, Japan
Phone : 81-3-5453-6711
FAX : 81-3-5453-6733

More Information

<https://www.ndk.com/en/>

